



AACSR IEC 61089 -Type A2/S1B Conductor, 77.32mm², Banana



Specifications

Conductor Name	Banana
Conductor Sectional Area	77.32 mm ²
Alloy Sectional Area	N/A mm ²
Steel Wires Sectional Area	N/A mm ²
Conductor Sectional Area	N/A mm ²
Alluminium Wires No.	6
Steel Wires No.	1
Alluminium Wire Diamenter	3.225 mm
Steel Wire Diameter	3.225 mm
Conductor Diameter	11.26 mm
Weight Alloy	N/A kg/km
Weight Steel	N/A kg/km
Conductor Weight	268 kg/km
Rated Strength	31.6 kN
Rated Strength Class A	N/A kN
Rated Strength Class B	N/A kN
DC Resistance@ 20°C	0.503 Ω/km
Current Capacity @75°C	167 A
Current Capacity @85°C	202 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.