

ZTACSR Conductor, 480.9mm²



The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.

Specifications

Stal Wires No.	26
Steel Wires No.	7
Stal Wire Diamenter	4.5 mm
Steel Wire Diameter	3.5 mm
Stal Wires Sectional Area	413.5 mm ²
Steel Wires Sectional Area	67.4 mm ²
Conductor Sectional Area	480.9 mm ²
Conductor Diameter	28.5 mm
Weight Stal	1141.9 kg/km
Weight Steel	526.2 kg/km
Conductor Weight	1668.1 kg/km
Rated Strength HS	N/A kN
Rated Strength EHS	N/A kN
Rated Strength	149.3 kN
Rated Strength UHS	167.8 kN
DC Resistance@ 20°C	0.071 Ω/km
Current Capacity @85°C	691 A
Current Capacity @150°C	1230 A
Current Capacity @210°C	1531 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.