

AACSR ABNT NBR 5369 Conductor, 450.73mm2 + 58.50mm2

Specifications

Conductor Name	N/A
Conductor Sectional Area	N/A mm²
Alloy Sectional Area	450.73 mm ²
Steel Wires Sectional Area	58.50 mm ²
Conductor Sectional Area	N/A mm²
Alluminium Wires No.	54
Steel Wires No.	19
Alluminium Wire Diamenter	3.26 mm
Steel Wire Diameter	1.98 mm
Conductor Diameter	29.46 mm
Weight Alloy	1245.8 kg/km
Weight Steel	457.9 kg/km
Conductor Weight	1703.7 kg/km
Rated Strength	N/A kN
Rated Strength Class A	208.9 kN
Rated Strength Class B	205.1 kN
DC Resistance@ 20°C	0.0749 Ω/km
Current Capacity @75°C	530 A
Current Capacity @85°C	676 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.