


## ACSS/TW Conductor, 931.46mm<sup>2</sup>, Pecos



### Specifications

Conductor Name	Pecos/ACSS/TW
Alluminium Wires Sectional Area	821.87 mm <sup>2</sup>
Steel Wires Sectional Area	109.59 mm <sup>2</sup>
Conductor Sectional Area	931.46 mm <sup>2</sup>
Alluminium Wires No.	39
Steel Wires No.	3
Alluminium Wire Diamenter	19 mm
Steel Wire Diameter	2.71 mm
Conductor Diameter	36.17 mm
Weight Aluminium	2281.30 kg/km
Weight Steel	857.75 kg/km
Conductor Weight	3139.05 kg/km
Rated Strength	201.87 kN
Rated Strength HS	221.59 kN
Rated Strength EHS	kN
Rated Strength UHS	255.57 kN
DC Resistance@ 20°C	0.03350 Ω/km
Current Capacity @85°C	1031 A
Current Capacity @200°C	2288 A
Current Capacity @250°C	2623 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.