


**ACSS** 



## ACSS Conductor, 307mm2, Squab





## **Specifications**

Conductor Name	Squab/ACSS
Conductor Sectional Area	307 mm <sup>2</sup>
Alluminium Wires No.	26
Steel Wires No.	7
Alluminium Wire Diamenter	3.87 mm
Steel Wire Diameter	3.01 mm
Conductor Diameter	24.54 mm
Weight Aluminium	848.0 kg/km
Weight Steel	389.1 kg/km
Conductor Weight	1237.1 kg/km
Rated Strength	87.9 kN
Rated Strength HS	96.8 kN
Rated Strength EHS	106.8 kN
Rated Strength UHS	112.3 kN
DC Resistance@ 20°C	0.090 Ω/km
Current Capacity @85°C	597 A
Current Capacity @150°C	1261 A
Current Capacity @210°C	1435 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.

www.polytrade.global 1 / 1