

PRODUCT DATA SHEET

EVERBUILD® Silicone Eater

A SILICONE SEALANT REMOVER

PRODUCT DESCRIPTION

EVERBUILD® Silicone Eater is specifically designed to remove all silicone based sealants and surface water repellents - cured and uncured. The product acts by denaturing silicone polymers making them easily water or solvent rinsable.

USES

- May be used on aluminum* and its alloys, copper and its alloys, iron, steels, glass, ceramics, epoxy composites, most plastics.
- Has little effect on rubber and other elastomers.
- Has little effect on most painted surfaces.

PRODUCT INFORMATION

Packaging	100 ml cartridge
Shelf Life	24 months from date of manufacture
Storage Conditions	Store in cool dry conditions between +5 °C and +25 °C. AVOID ALL CONTACT WITH MOISTURE
Colour	Amber to dark tan
Appearance / Colour	Paste
Density	~0.87 g/cm ³
Flash Point	~70 °C
Viscosity	1400+/- 600 poise @ 25°C.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

CHARACTERISTICS / ADVANTAGES

- Readily denatures silicone.
- Ready for use gel - may be used vertically as well as horizontally.
- Water clean-up.

Solubility	Insoluble in water
pH	3 in 100 g/L water
Boiling Point	205°C
Vapour pressure	0.15 Kpa at 20 °C
Auto IGN	>200 °C in water
Explosion Limits	N/D

*TEST A SMALL AREA BEFORE USE. In all cases, apply a small test patch to an inconspicuous area. Leave for 2 hours min and rinse off. Check for staining/corrosion before attempting the whole job.

* May attack nylon, certain fabrics/textiles and coloured anodised aluminum (used as a trim around showers), PU coated (re-enameled) baths, fluoroacrylics, chipped surfaces.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

All surfaces must be clean, dry and dust free. Cut away as much as possible of the silicone sealant using a sharp knife. Protect surrounding areas with impervious masking tape.

APPLICATION METHOD / TOOLS

Cut the tip of the cartridge taking care not to damage the thread. Apply nozzle and cut at an angle of 45 ° with an opening slightly larger than the gap to be sealed. Apply using a standard sealant gun. Best results will be obtained by keeping an even pressure on the trigger and keeping the gun at a constant angle to the surface being sealed.

(a) Removing Silicone sealants from baths/showers etc:

Spread the bead over the entire area which requires treatment (use masking tape to protect surrounding areas). A coating of at least twice the thickness of the underlying silicone should be applied.

The dwell time required may be varied between 2 hours to 4 hours depending primarily on the characteristics of the underlying silicone and the substrate from which it is to be debonded. Repeat application if necessary.

Wash off with water after 4 hours maximum.

Note: The product specifically removes silicone products. It may only have a softening effect on acrylics, GP mastics and butyl sealant.

NB ALWAYS TEST A SMALL AREA FIRST TO ENSURE COMPATIBILITY (INCLUDING RUN OFF AREA). THE PRODUCT IS IRREVERSIBLY NULLIFIED BY CONTACT WITH WATER. ENSURE SURFACES ARE DRY.

(b) Removing Silicone Water Repellent overspray from windows and frames:

Apply as in (a) to window panes, frames, sills etc and allow a dwell time of 10 minutes. Wash off with white spirit or water. Repeat if necessary.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

Product Data Sheet

EVERBUILD® Silicone
Eater

August 2022, Version
02.01

020516020000000030
2/2



BUILDING TRUST

