


MMMP 24/M12 1.2kN , Cable Diameter: 7.5 mm, Core Type: G.655D, Armor Type: NARP, Jacket Type: SJ, Jacket Material: HDPE, Fiber & Tube CC: CC-IEC-60304 , Cable Color: Black



Description

Micro-Module Multi-Purpose Cables (MMMP) are used in various communication networks, designed for aerial or duct installation. Easy strippable micro modules allow a fast installation without a need for special tools. Due to our new technology, the cables show good flexibility and endurance to repeated bending, and great water blocking function. The glass yarns helps the cable to have good tensile performance and temperature performance under extreme weathers, but also rodent protection under dielectric conditions. This cable contains fibers made of high pure silica and germanium doped silica.

Standards

IEC60794-1
IEC60794-2
IEC60304
ITU-T
EIA-TIA
BS EN 187000
DIN0888
XP C 93-850-3-25

Construction

Central tube with Micro-Modules containing fibers, gel filled;
Water swellable yarns;
Water blocking tape;
Glass Yarns or Aramid Yarns as peripheral strength member;
Ripcords;
FRP Rods;
Outer Sheath (UV Resistance, Rodent Protect);

Cable Characteristics

Fiber Count	24
Modularity	M12
Tube Count layer 1	2
Tube Count layer 2	N/A
Tube Count layer 3	N/A
Filler Count	0
Cable Diameter	7.5
Cable Diameter Tolerance	± 0.5
Cable Weight	56
Cable Weight Tolerance	± 5
Rate Tensile Strength (RTS)	3
Maximum Allowable Tension (MAT) (40%RTS)	1.2
Everyday Stress (EDS) (20%RTS)	0.6
Strain Margin Strength (60%RTS)	1.8
Crush	2000
Minimum Bending Radius (Installing)	20xD
Minimum Bending Radius (Operating)	10xD
Installation Tensile Strength (≤20%RTS)	0.6
Working Temperature	(-)40 >< (+)70
Installation Temperature	(-)10 >< (+)60
Aarmor Type	NARP
Jacket Type	SJ
Jacket Material	HDPE
TRS	N/A
Fiber & Tube CC	CC-IEC-60304
Packing	Wooden Drum
Delivery Lengths	To be confirmed by offer
Delivery Length Tolerance	±5

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.

Optical Fiber Core Characteristics

Core Type	G.655D
Attenuation Coefficient at 1310 nm Max.	N/A
Attenuation Coefficient at 1550 nm Max.	≤ 0.22
Attenuation Coefficient at 1625 nm Max.	≤ 0.24
Chromatic Dispersion between 1285 - 1330 nm	N/A
Chromatic Dispersion at 1550 nm	≤ 6
Chromatic Dispersion at 1625 nm	≤ 11
Point Discontinuity at 1310 & 1550 nm	≤ 0.05
Polarization Mode Dispersion (PMD Individual)	≤ 0.1
Polarization Mode Dispersion (Link Design)	≤ 0.08
The uniformity attenuation at any projected wavelength	≤ 0.05
Cable Cut off Wavelength (λ_{cc})	≤ 1450
Mode Field Diameter at 1310 nm	N/A
Mode Field Diameter at 1550 nm	9.6 ± 0.4
Cladding Diameter	125.0 ± 0.7
Cladding Non-Circularity	≤ 0.7
Core / Cladding Concentricity error	≤ 0.6
Coating Diameter	255 ± 10
Coating / Cladding Concentricity error	≤ 12

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.