



AACSR ABNT NBR 5369 Conductor, 250.15mm² + 40.67mm²



Specificații

Nume Conductor	N/A
Aria Secțională Conductor	N/A mm ²
Aria Secțională Aliaj	250.15 mm ²
Aria Secțională Fire Oțel	40.67 mm ²
Aria Secțională Conductor	N/A mm ²
Număr Fire Aluminiu	26
Număr Fire Oțel	7
Diametru Fir Aluminiu	3.50 mm
Diametru Fir Oțel	2.72 mm
Diametru Conductor	22.16 mm
Greutate Aliaj	689.7 kg/km
Greutate Oțel	317.7 kg/km
Greutate Conductor	1007.4 kg/km
Rezistență Nominală	N/A kN
Clasa A Rezistență Nominală	128.8 kN
Clasa B Rezistență Nominală	126.1 kN
Rezistență DC @ 20°C	0.1346 Ω/km
Capacitate Curent @75°C	387 A
Capacitate Curent @85°C	483 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.