

ACSS/TW Conductor, 516.96mm², Rail



Specificații

Nume Conductor	Rail/ACSS/TW
Suprafață Secțională Fire Aluminiu	483.42 mm ²
Suprafață Secțională Fire Oțel	33.54 mm ²
Suprafață Secțională Conductor	516.96 mm ²
Nr. Fire Aluminiu	32
Nr. Fire Oțel	3
Diametru Fir Aluminiu	7 mm
Diametru Fir Oțel	2.47 mm
Diametru Conductor	26.95 mm
Greutate Aluminiu	1339.30 kg/km
Greutate Oțel	262.00 kg/km
Greutate Conductor	1601.30 kg/km
Rezistență Nominală	75.14 kN
Rezistență Nominală HS	81.18 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	91.57 kN
Rezistență DC @ 20°C	0.05740 Ω/km
Capacitate Curent @ 85°C	748 A
Capacitate Curent @ 200°C	1598 A
Capacitate Curent @ 250°C	1821 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.