

## ACSS/TW Conductor, 705.42mm<sup>2</sup>, Yukon



### Specificații

Nume Conductor	Yukon/ACSS/TW
Suprafață Secționată Fire Aluminiu	625.10 mm <sup>2</sup>
Suprafață Secționată Fire Oțel	80.32 mm <sup>2</sup>
Suprafață Secționată Conductor	705.42 mm <sup>2</sup>
Nr. Fire Aluminiu	38
Nr. Fire Oțel	3
Diametru Fir Aluminiu	19 mm
Diametru Fir Oțel	2.32 mm
Diametru Conductor	31.62 mm
Greutate Aluminiu	1735.90 kg/km
Greutate Oțel	628.63 kg/km
Greutate Conductor	2364.53 kg/km
Rezistență Nominală	149.26 kN
Rezistență Nominală HS	163.71 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	188.61 kN
Rezistență DC @ 20°C	0.04430 Ω/km
Capacitate Curent @ 85°C	877 A
Capacitate Curent @ 200°C	1911 A
Capacitate Curent @ 250°C	2184 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.