

KTACSR/TW Conductor, 788.54mm²



Specificații

Suprafață Secțională Fire Ktal	737.4 mm ²
Suprafață Secțională Fire Oțel	51.14 mm ²
Suprafață Secțională Conductor	788.54 mm ²
Nr. Fire Ktal	36
Nr. Fire Straturi Ktal	3
Nr. Fire Oțel	7
Diametru Fir Oțel	3.05 mm
Diametru Conductor	32.60 mm
Greutate Ktal	2043.0 kg/km
Greutate Oțel	399.61 kg/km
Greutate Conductor	2442.6 kg/km
Rezistență Nominală	221.96 kN
Rezistență Nominală HS	229.12 kN
Rezistență Nominală EHS	234.24 kN
Rezistență Nominală UHS	236.03 kN
Rezistență DC @ 20°C	0.0435 Ω/km
Capacitate Curent @ 85°C	890 A
Capacitate Curent @ 150°C	1606 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.