

KTACSR/TW Conductor, 930.65mm²



Specificații

Suprafață Secționată Fire Ktal	821.87 mm ²
Suprafață Secționată Fire Oțel	108.79 mm ²
Suprafață Secționată Conductor	930.65 mm ²
Nr. Fire Ktal	39
Nr. Fire Straturi Ktal	3
Nr. Fire Oțel	19
Diametru Fir Oțel	2.70 mm
Diametru Conductor	35.40 mm
Greutate Ktal	2277.0 kg/km
Greutate Oțel	852.87 kg/km
Greutate Conductor	3130.0 kg/km
Rezistență Nominală	315.95 kN
Rezistență Nominală HS	330.09 kN
Rezistență Nominală EHS	341.51 kN
Rezistență Nominală UHS	345.32 kN
Rezistență DC @ 20°C	0.0391 Ω/km
Capacitate Curent @ 85°C	954 A
Capacitate Curent @ 150°C	1736 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.