


TACSR Conductor, 96.98mm²



Specificații

Număr Fire Tal	6
Număr Fire Oțel	1
Diametru Fir Tal	4.20 mm
Diametru Fir Oțel	4.20 mm
Suprafață Secțională Fire Tal	83.13 mm ²
Suprafață Secțională Fire Oțel	13.85 mm ²
Suprafață Secțională Conductor	96.98 mm ²
Diametru Conductor	12.60 mm
Greutate Tal	228.1 kg/km
Greutate Oțel	107.8 kg/km
Greutate Conductor	335.9 kg/km
Rezistență Nominală HS	31.8 kN
Rezistență Nominală EHS	33.3 kN
Rezistență Nominală	29.4 kN
Rezistență Nominală UHS	33.7 kN
Rezistență DC @ 20°C	0.3509 Ω/km
Capacitate Curent @ 85°C	246 A
Capacitate Curent @ 150°C	410 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.