


ACSS Conductor, 152mm², Ostrich



Specificații

Nume Conductor	Ostrich/ACSS
Aria sectiunii transversale	152 mm ²
Nr. fire aluminiu	26
Nr. fire otel	7
Diametru fir aluminiu	2.73 mm
Diametru fir otel	2.12 mm
Diametru Conductor	17.27 mm
Greutate Aluminiu	420.6 kg/km
Greutate Otel	193.0 kg/km
Greutate Conductor	613.6 kg/km
Rezistenta Nominala	44.6 kN
Rezistenta Nominala HS	48.8 kN
Rezistenta Nominala EHS	53.9 kN
Rezistenta Nominala UHS	57.3 kN
Rezistenta CC @ 20°C	0.1808 Ω/km
Capacitate Curent @ 85°C	391 A
Capacitate curent @ 150°C	798 A
Capacitate Curent @ 210°C	903 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.