


ACSS Conductor, 282mm², Parakeet



Specificații

Nume Conductor	Parakeet/ACSS
Aria sectiunii transversale	282 mm ²
Nr. fire aluminiu	24
Nr. fire otel	7
Diametru fir aluminiu	3.87 mm
Diametru fir otel	2.58 mm
Diametru Conductor	23.22 mm
Greutate Aluminiu	779.9 kg/km
Greutate Otel	285.9 kg/km
Greutate Conductor	1065.8 kg/km
Rezistenta Nominala	67.9 kN
Rezistenta Nominala HS	74.5 kN
Rezistenta Nominala EHS	81.8 kN
Rezistenta Nominala UHS	85.8 kN
Rezistenta CC @ 20°C	0.098 Ω/km
Capacitate Curent @ 85°C	565 A
Capacitate curent @ 150°C	1187 A
Capacitate Curent @ 210°C	1349 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.