


TACSR Conductor, 297.57mm²



Specificații

Număr Fire Tal	30
Număr Fire Oțel	7
Diametru Fir Tal	3.20 mm
Diametru Fir Oțel	3.20 mm
Suprafață Secțională Fire Tal	241.27 mm ²
Suprafață Secțională Fire Oțel	56.30 mm ²
Suprafață Secțională Conductor	297.57 mm ²
Diametru Conductor	22.40 mm
Greutate Tal	665.5 kg/km
Greutate Oțel	439.9 kg/km
Greutate Conductor	1105.4 kg/km
Rezistență Nominală HS	116.8 kN
Rezistență Nominală EHS	122.4 kN
Rezistență Nominală	108.9 kN
Rezistență Nominală UHS	124.4 kN
Rezistență DC @ 20°C	0.1215 Ω/km
Capacitate Curent @ 85°C	504 A
Capacitate Curent @ 150°C	877 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.