


TACSR Conductor, 708.28mm²



Specificații

Număr Fire Tal	54
Număr Fire Oțel	19
Diametru Fir Tal	3.85 mm
Diametru Fir Oțel	2.31 mm
Suprafață Secțională Fire Tal	628.65 mm ²
Suprafață Secțională Fire Oțel	79.63 mm ²
Suprafață Secțională Conductor	708.28 mm ²
Diametru Conductor	34.65 mm
Greutate Tal	1738.8 kg/km
Greutate Oțel	624.3 kg/km
Greutate Conductor	2363.1 kg/km
Rezistență Nominală HS	212.2 kN
Rezistență Nominală EHS	220.6 kN
Rezistență Nominală	201.9 kN
Rezistență Nominală UHS	223.4 kN
Rezistență DC @ 20°C	0.0468 Ω/km
Capacitate Curent @ 85°C	870 A
Capacitate Curent @ 150°C	1579 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.