

ACSS/TW Conductor, 364.14mm², Rook



Specificații

Nume Conductor	Rook/ACSS/TW
Suprafață Secțională Fire Aluminiu	322.26 mm ²
Suprafață Secțională Fire Oțel	41.88 mm ²
Suprafață Secțională Conductor	364.14 mm ²
Nr. Fire Aluminiu	20
Nr. Fire Oțel	2
Diametru Fir Aluminiu	7 mm
Diametru Fir Oțel	2.76 mm
Diametru Conductor	22.61 mm
Greutate Aluminiu	889.80 kg/km
Greutate Oțel	327.13 kg/km
Greutate Conductor	1216.93 kg/km
Rezistență Nominală	77.61 kN
Rezistență Nominală HS	85.15 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	98.13 kN
Rezistență DC @ 20°C	0.08530 Ω/km
Capacitate Curent @ 85°C	602 A
Capacitate Curent @ 200°C	1260 A
Capacitate Curent @ 250°C	1432 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.