

ACSS/TW Conductor, 374.75mm², Grosbeak



Specificații

Nume Conductor	Grosbeak/ACSS/TW
Suprafață Secțională Fire Aluminiu	322.26 mm ²
Suprafață Secțională Fire Oțel	52.49 mm ²
Suprafață Secțională Conductor	374.75 mm ²
Nr. Fire Aluminiu	20
Nr. Fire Oțel	2
Diametru Fir Aluminiu	7 mm
Diametru Fir Oțel	3.09 mm
Diametru Conductor	23.06 mm
Greutate Aluminiu	890.50 kg/km
Greutate Oțel	410.03 kg/km
Greutate Conductor	1300.53 kg/km
Rezistență Nominală	92.58 kN
Rezistență Nominală HS	99.93 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	116.20 kN
Rezistență DC @ 20°C	0.08500 Ω/km
Capacitate Curent @ 85°C	605 A
Capacitate Curent @ 200°C	1270 A
Capacitate Curent @ 250°C	1443 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.