

ACSS/TW Conductor, 818.33mm², Merrimack



Specificații

Nume Conductor	Merrimack/ACSS/TW
Suprafață Secțională Fire Aluminiu	725.81 mm ²
Suprafață Secțională Fire Oțel	92.52 mm ²
Suprafață Secțională Conductor	818.33 mm ²
Nr. Fire Aluminiu	39
Nr. Fire Oțel	3
Diametru Fir Aluminiu	19 mm
Diametru Fir Oțel	2.49 mm
Diametru Conductor	34.04 mm
Greutate Aluminiu	2017.90 kg/km
Greutate Oțel	724.14 kg/km
Greutate Conductor	2742.04 kg/km
Rezistență Nominală	172.26 kN
Rezistență Nominală HS	188.92 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	217.60 kN
Rezistență DC @ 20°C	0.03810 Ω/km
Capacitate Curent @ 85°C	957 A
Capacitate Curent @ 200°C	2107 A
Capacitate Curent @ 250°C	2412 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.