

## AAAC-Z as per NBN C 34-100 Conductor, 461.73mm2, 255-2Z

## **Specifications**

Conductor Code	255-2Z
Round Wires Sectional Area	125.5 mm <sup>2</sup>
Round Wires No.	19
Z-Shaped Wires Layers No.	2
Z-Shaped Wires No.	42
Conductor Sectional Area	461.73 mm <sup>2</sup>
Z-Shaped Wires Diameter	3.19 mm
Conductor Diameter	26.10 mm
Conductor Weight	1275.0 kg/km
Z-Shaped Wires Sectional Area	336.23 mm <sup>2</sup>
Round Wires Diameter	2.90 mm
Mass Of Grease (Min.)	24.1 kg/km
Mass Of Grease (Max.)	36.2 kg/km
Rated Strength	150.06 kN
DC Resistance@ 20°C	0.0722 Ω/km
Current Capacity @75°C	538 A
Current Capacity @85°C	680 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.