

AACSR IEC 61089 -Type A2/S1A Conductor, 276mm²



Specificații

Nume Conductor	N/A
Aria Secțională Conductor	276 mm ²
Aria Secțională Aliaj	224 mm ²
Aria Secțională Fire Oțel	N/A mm ²
Aria Secțională Conductor	52 mm ²
Număr Fire Aluminiu	30
Număr Fire Oțel	7
Diametru Fir Aluminiu	3.08 mm
Diametru Fir Oțel	3.08 mm
Diametru Conductor	21.57 mm
Greutate Aliaj	N/A kg/km
Greutate Oțel	N/A kg/km
Greutate Conductor	1025.01 kg/km
Rezistență Nominală	139.01 kN
Clasa A Rezistență Nominală	N/A kN
Clasa B Rezistență Nominală	N/A kN
Rezistență DC @ 20°C	0.1510 Ω/km
Capacitate Curent @75°C	385 A
Capacitate Curent @85°C	480 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.