


AACSR IEC 61089 -Type A3/S3A Conductor, 356.3mm², Lime



Specificații

Nume Conductor	Lime
Aria Secțională Conductor	356.3 mm ²
Aria Secțională Aliaj	N/A mm ²
Aria Secțională Fire Oțel	N/A mm ²
Aria Secțională Conductor	N/A mm ²
Număr Fire Aluminiu	30
Număr Fire Oțel	7
Diametru Fir Aluminiu	3.500 mm
Diametru Fir Oțel	3.500 mm
Diametru Conductor	24.53 mm
Greutate Aliaj	N/A kg/km
Greutate Oțel	N/A kg/km
Greutate Conductor	1320 kg/km
Rezistență Nominală	404 kN
Clasa A Rezistență Nominală	N/A kN
Clasa B Rezistență Nominală	N/A kN
Rezistență DC @ 20°C	0.116 Ω/km
Capacitate Curent @75°C	422 A
Capacitate Curent @85°C	531 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.