

ACSS/TW Conductor, 446.56mm², Puffin



Specificații

Nume Conductor	Puffin/ACSS/TW
Suprafață Secționată Fire Aluminiu	402.84 mm ²
Suprafață Secționată Fire Oțel	43.72 mm ²
Suprafață Secționată Conductor	446.56 mm ²
Nr. Fire Aluminiu	18
Nr. Fire Oțel	2
Diametru Fir Aluminiu	7 mm
Diametru Fir Oțel	2.82 mm
Diametru Conductor	24.89 mm
Greutate Aluminiu	1111.50 kg/km
Greutate Oțel	341.51 kg/km
Greutate Conductor	1453.01 kg/km
Rezistență Nominală	84.85 kN
Rezistență Nominală HS	92.72 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	106.27 kN
Rezistență DC @ 20°C	0.06860 Ω/km
Capacitate Curent @ 85°C	684 A
Capacitate Curent @ 200°C	1447 A
Capacitate Curent @ 250°C	1646 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.