

ACSS/TW Conductor, 553.16mm², Columbia



Specificații

Nume Conductor	Columbia/ACSS/TW
Suprafață Secțională Fire Aluminiu	489.61 mm ²
Suprafață Secțională Fire Oțel	63.55 mm ²
Suprafață Secțională Conductor	553.16 mm ²
Nr. Fire Aluminiu	21
Nr. Fire Oțel	2
Diametru Fir Aluminiu	7 mm
Diametru Fir Oțel	3.40 mm
Diametru Conductor	27.74 mm
Greutate Aluminiu	1351.20 kg/km
Greutate Oțel	496.43 kg/km
Greutate Conductor	1847.63 kg/km
Rezistență Nominală	117.81 kN
Rezistență Nominală HS	126.71 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	146.41 kN
Rezistență DC @ 20°C	0.05840 Ω/km
Capacitate Curent @ 85°C	757 A
Capacitate Curent @ 200°C	1621 A
Capacitate Curent @ 250°C	1848 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.