

KTACSR/TW Conductor, 327.42mm²



Specificații

Suprafață Secționată Fire Ktal	586.76 mm ²
Suprafață Secționată Fire Oțel	41.28 mm ²
Suprafață Secționată Conductor	628.03 mm ²
Nr. Fire Ktal	33
Nr. Fire Straturi Ktal	3
Nr. Fire Oțel	7
Diametru Fir Oțel	2.74 mm
Diametru Conductor	29.10 mm
Greutate Ktal	1625.7 kg/km
Greutate Oțel	322.50 kg/km
Greutate Conductor	1948.2 kg/km
Rezistență Nominală	178.99 kN
Rezistență Nominală HS	184.36 kN
Rezistență Nominală EHS	188.69 kN
Rezistență Nominală UHS	190.13 kN
Rezistență DC @ 20°C	0.0548 Ω/km
Capacitate Curent @ 85°C	778 A
Capacitate Curent @ 150°C	1387 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.