

ZTACSR Conductor, 766.6mm²



The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.

Specificații

Număr Fire Stal	54
Număr Fire Oțel	7
Diametru Fir Stal	4.0 mm
Diametru Fir Oțel	4.0 mm
Suprafață Secționată Fire Stal	678.6 mm ²
Suprafață Secționată Fire Oțel	88.0 mm ²
Suprafață Secționată Conductor	766.6 mm ²
Diametru Conductor	36.0 mm
Greutate Stal	1877.0 kg/km
Greutate Oțel	687.3 kg/km
Greutate Conductor	2564.2 kg/km
Rezistență Nominală HS	N/A kN
Rezistență Nominală EHS	N/A kN
Rezistență Nominală	210.8 kN
Rezistență Nominală UHS	238.1 kN
Rezistență DC @ 20°C	0.043 Ω/km
Capacitate Curent @ 85°C	909 A
Capacitate Curent @ 150°C	1658 A
Capacitate Curent @ 210°C	2079 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.