


ACSS Conductor, 135mm², Junco



Specificații

| | |
|-----------------------------|---------------------|
| Nume Conductor | Junco/ACSS |
| Aria secțiunii transversale | 135 mm ² |
| Nr. fire aluminiu | 30 |
| Nr. fire otel | 7 |
| Diametru fir aluminiu | 2.40 mm |
| Diametru fir otel | 2.40 mm |
| Diametru Conductor | 16.76 mm |
| Greutate Aluminiu | 374.9 kg/km |
| Greutate Otel | 247.4 kg/km |
| Greutate Conductor | 622.3 kg/km |
| Rezistentă Nominală | 52.5 kN |
| Rezistentă Nominală HS | 58.2 kN |
| Rezistentă Nominală EHS | 64.5 kN |
| Rezistentă Nominală UHS | 68.0 kN |
| Rezistentă CC @ 20°C | 0.2018 Ω/km |
| Capacitate Curent @ 85°C | 368 A |
| Capacitate curent @ 150°C | 748 A |
| Capacitate Curent @ 210°C | 846 A |

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.