


ACSS Conductor, 242mm², Hawk



Specificații

Nume Conductor	Hawk/ACSS
Aria secțiunii transversale	242 mm ²
Nr. fire aluminiu	26
Nr. fire otel	7
Diametru fir aluminiu	3.44 mm
Diametru fir otel	2.67 mm
Diametru Conductor	21.79 mm
Greutate Aluminiu	668.6 kg/km
Greutate Otel	306.1 kg/km
Greutate Conductor	974.7 kg/km
Rezistentă Nominală	69.2 kN
Rezistentă Nominală HS	76.2 kN
Rezistentă Nominală EHS	84.1 kN
Rezistentă Nominală UHS	88.4 kN
Rezistentă CC @ 20°C	0.1135 Ω/km
Capacitate Curent @ 85°C	518 A
Capacitate curent @ 150°C	1080 A
Capacitate Curent @ 210°C	1227 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.