


ACSS Conductor, 307mm², Squab



Specificații

Nume Conductor	Squab/ACSS
Aria secțiunii transversale	307 mm ²
Nr. fire aluminiu	26
Nr. fire otel	7
Diametru fir aluminiu	3.87 mm
Diametru fir otel	3.01 mm
Diametru Conductor	24.54 mm
Greutate Aluminiu	848.0 kg/km
Greutate Otel	389.1 kg/km
Greutate Conductor	1237.1 kg/km
Rezistentă Nominală	87.9 kN
Rezistentă Nominală HS	96.8 kN
Rezistentă Nominală EHS	106.8 kN
Rezistentă Nominală UHS	112.3 kN
Rezistentă CC @ 20°C	0.090 Ω/km
Capacitate Curent @ 85°C	597 A
Capacitate curent @ 150°C	1261 A
Capacitate Curent @ 210°C	1435 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.