


ACSS Conductor, 338mm², Gannet



Specificații

Nume Conductor	Gannet/ACSS
Aria sectiunii transversale	338 mm ²
Nr. fire aluminiu	26
Nr. fire otel	7
Diametru fir aluminiu	4.07 mm
Diametru fir otel	3.16 mm
Diametru Conductor	25.76 mm
Greutate Aluminiu	934.3 kg/km
Greutate Otel	428.8 kg/km
Greutate Conductor	1363.1 kg/km
Rezistenta Nominala	96.9 kN
Rezistenta Nominala HS	104.6 kN
Rezistenta Nominala EHS	116.1 kN
Rezistenta Nominala UHS	121.6 kN
Rezistenta CC @ 20°C	0.081 Ω/km
Capacitate Curent @ 85°C	633 A
Capacitate curent @ 150°C	1343 A
Capacitate Curent @ 210°C	1529 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.