


ACSS Conductor, 1031mm², Mockingbird



Specificații

Nume Conductor	Mockingbird/ACSS
Aria secțiunii transversale	1031 mm ²
Nr. fire aluminiu	72
Nr. fire otel	7
Diametru fir aluminiu	4.27 mm
Diametru fir otel	2.85 mm
Diametru Conductor	42.70 mm
Greutate Aluminiu	2865.6 kg/km
Greutate Otel	348.8 kg/km
Greutate Conductor	3214.4 kg/km
Rezistentă Nominală	122.4 kN
Rezistentă Nominală HS	130.4 kN
Rezistentă Nominală EHS	139.3 kN
Rezistentă Nominală UHS	144.2 kN
Rezistentă CC @ 20°C	0.027 Ω/km
Capacitate Curent @ 85°C	1178 A
Capacitate curent @ 150°C	2693 A
Capacitate Curent @ 210°C	3100 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.