


## ACSR-Z Conductor, 179.32mm<sup>2</sup>



### Specifications

Steel Wires No.	7
Steel Wire Diameter	3.3 mm
Round Al. Wires No.	N/A
Round Al. Wires Diameter	N/A mm
Z-Shaped Wires Layers No.	1
Z-Shaped Wires No.	12
Z-Shaped Wires Diameter	3.56 mm
Steel Wires Sectional Area	59.87 mm <sup>2</sup>
Round Wires Sectional Area	N/A mm <sup>2</sup>
Z-Shaped Wires Sectional Area	119.45 mm <sup>2</sup>
Conductor Sectional Area	179.32 mm <sup>2</sup>
Conductor Diameter	16.5 mm
Conductor Weight	797.1 kg/km
Rated Strength	107.72 kN
DC Resistance@ 20°C	0.2414 Ω/km
Current Capacity @75°C	255 A
Current Capacity @85°C	313 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.