

## ZTACSR Conductor, 900.5mm<sup>2</sup>



The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.

Specifications

Stal Wires No.	54
Steel Wires No.	19
Stal Wire Diamenter	4.3 mm
Steel Wire Diameter	2.6 mm
Stal Wires Sectional Area	798.9 mm <sup>2</sup>
Steel Wires Sectional Area	101.7 mm <sup>2</sup>
Conductor Sectional Area	900.5 mm <sup>2</sup>
Conductor Diameter	39.1 mm
Weight Stal	2209.6 kg/km
Weight Steel	796.9 kg/km
Conductor Weight	3006.5 kg/km
Rated Strength HS	N/A kN
Rated Strength EHS	N/A kN
Rated Strength	257.1 kN
Rated Strength UHS	284.6 kN
DC Resistance@ 20°C	0.037 Ω/km
Current Capacity @85°C	999 A
Current Capacity @150°C	1840 A
Current Capacity @210°C	2313 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.