

PRODUCT DATA SHEET

Sikagard® Wood Preserver

Prevents wood rot and decay

PRODUCT DESCRIPTION

Sikagard® Wood Preserver is a low-odour solution based on Micro-fine active technology. The fungicides and algaecides present in the formulation are finely dispersed so that wood penetration, and hence effectiveness, is much greater than standard wood preservation products. Sikagard® Wood Preserver is fast-drying and non-flammable; and application to wet timbers is possible without loss of performance. It is specifically designed to deeply penetrate all wood and joinery to give long lasting protection from damage caused by wet rot, dry rot, decay and fungi.

USES

For use on interior or exterior rough-sawn or planed timber such as:

- Floorboards
- Joists
- Roof timbers
- Window frames and doors

CHARACTERISTICS / ADVANTAGES

- Non-flammable.
- Internal and external use.
- Can be applied to damp timbers.

PRODUCT INFORMATION

Packaging	5 L Tin
Shelf Life	Use within 2 years of manufacture.
Storage Conditions	Store at +5 °C to +25 °C in original containers away from children.
Appearance / Colour	Clear liquid

APPLICATION INFORMATION

Consumption	For preventative effect against insects and wood rotting fungi apply 250 ml per square metre. Joinery, floorboards, roof joists etc: Apply 1 litre of product per 3 - 4 m ² of surface. Ideally this should be applied as 2 - 3 even coats, leaving at least 2 hours, or until previous coat is dry, between applications. Timber not in ground contact: Apply 2 even coats by brush or spray application. Coverage: 3 - 4 m ² per litre.
--------------------	---

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Ready to use - do not dilute.
- Always use coarse rather than fine mist generators.
- Do not apply to surfaces on which food is prepared.
- Avoid contact with bitumen, roofing felt or plastics.
- External timbers must be over coated to reduce environmental impact
- It is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services Department for advice.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

Shake well before use. Apply by brush, spray or dipping. Apply a minimum of two coats if brushing or spraying. The second coat should be applied after the first coat has dried. Pay particular attention to thoroughly soaking of the end grain. Where possible, and for maximum protection, dip the end grains of the timber for a minimum of 3 minutes.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited