

AAAC-Z as per NBN C 34-100 Conductor, 511.25mm², 504-2Z



Specificații

Cod Conductor	504-2Z
Secțiune Fire Rotunde	138.82 mm ²
Număr Fire Rotunde	19
Număr Straturi Fire În Formă De Z	2
Număr Fire În Formă De Z	42
Secțiune Conductor	511.25 mm ²
Diametru Fire În Formă De Z	3.36 mm
Diametru Conductor	27.45 mm
Greutate Conductor	1412.0 kg/km
Secțiune Fire În Formă De Z	372.44 mm ²
Diametru Fire Rotunde	3.05 mm
Masă De Vaselină (Min.)	26.7 kg/km
Masă De Vaselină (Max.)	40.1 kg/km
Rezistență Mecanică Nominală	166.16 kN
Rezistență Curent Continu @ 20°C	0.0652 Ω/km
Capacitate Curent @75°C	569 A
Capacitate Curent @85°C	722 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.