

AACSR ASTM B 711 Conductor, 209mm²



Specificații

Nume Conductor	N/A
Aria Secționă Conductor	209 mm ²
Aria Secționă Aliaj	180 mm ²
Aria Secționă Fire Oțel	N/A mm ²
Aria Secționă Conductor	29 mm ²
Număr Fire Aluminiu	26
Număr Fire Oțel	7
Diametru Fir Aluminiu	2.97 mm
Diametru Fir Oțel	2.31 mm
Diametru Conductor	18.81 mm
Greutate Aliaj	N/A kg/km
Greutate Oțel	N/A kg/km
Greutate Conductor	731.00 kg/km
Rezistență Nominală	95.10 kN
Clasa A Rezistență Nominală	N/A kN
Clasa B Rezistență Nominală	N/A kN
Rezistență DC @ 20°C	0.1868 Ω/km
Capacitate Curent @75°C	423 A
Capacitate Curent @85°C	524 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.