

AACSR IEC 61089 -Type A2/S1B Conductor, 199.53mm² + 46.57mm²



Specificații

Nume Conductor	N/A
Aria Secționă Conductor	N/A mm ²
Aria Secționă Aliaj	199.53 mm ²
Aria Secționă Fire Oțel	46.57 mm ²
Aria Secționă Conductor	N/A mm ²
Număr Fire Aluminiu	30
Număr Fire Oțel	7
Diametru Fir Aluminiu	2.91 mm
Diametru Fir Oțel	2.91 mm
Diametru Conductor	20.153 mm
Greutate Aliaj	551.3 kg/km
Greutate Oțel	363.8 kg/km
Greutate Conductor	915.3 kg/km
Rezistență Nominală	N/A kN
Clasa A Rezistență Nominală	124.5 kN
Clasa B Rezistență Nominală	121.4 kN
Rezistență DC @ 20°C	0.1691 Ω/km
Capacitate Curent @75°C	341 A
Capacitate Curent @85°C	424 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.