

## AACSR IEC 61089 -Type A2/S1B Conductor, 450.74mm<sup>2</sup> + 58.51mm<sup>2</sup>



### Specificații

Nume Conductor	N/A
Aria Secționă Conductor	N/A mm <sup>2</sup>
Aria Secționă Aliaj	450.74 mm <sup>2</sup>
Aria Secționă Fire Oțel	58.51 mm <sup>2</sup>
Aria Secționă Conductor	N/A mm <sup>2</sup>
Număr Fire Aluminiu	54
Număr Fire Oțel	19
Diametru Fir Aluminiu	3.26 mm
Diametru Fir Oțel	1.99 mm
Diametru Conductor	29.47 mm
Greutate Aliaj	1245.9 kg/km
Greutate Oțel	457.10 kg/km
Greutate Conductor	1703.8 kg/km
Rezistență Nominală	N/A kN
Clasa A Rezistență Nominală	208.10 kN
Clasa B Rezistență Nominală	205.2 kN
Rezistență DC @ 20°C	0.0749 Ω/km
Capacitate Curent @75°C	530 A
Capacitate Curent @85°C	676 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.