


AACSR IEC 61089 -Type A3/S1B Conductor, 1211mm²



Specificații

Nume Conductor	N/A
Aria Secționă Conductor	1211 mm ²
Aria Secționă Aliaj	1120 mm ²
Aria Secționă Fire Oțel	N/A mm ²
Aria Secționă Conductor	91 mm ²
Număr Fire Aluminiu	84
Număr Fire Oțel	19
Diametru Fir Aluminiu	4.126 mm
Diametru Fir Oțel	2.47 mm
Diametru Conductor	45.34 mm
Greutate Aliaj	N/A kg/km
Greutate Oțel	N/A kg/km
Greutate Conductor	3816.03 kg/km
Rezistență Nominală	439.03 kN
Clasa A Rezistență Nominală	N/A kN
Clasa B Rezistență Nominală	N/A kN
Rezistență DC @ 20°C	0.0302 Ω/km
Capacitate Curent @75°C	866 A
Capacitate Curent @85°C	1151 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.