


ACSS/AW Conductor, 307mm², Squab



Specificații

| | |
|------------------------------|---------------------|
| Nume Conductor | Squab/ACSS/AW |
| Suprafață Secționă Conductor | 307 mm ² |
| Nr. Fire Aluminiu | 26 |
| Nr. Fire ACS | 7 |
| Diametru Fir Aluminiu | 3.87 mm |
| Diametru Fir ACS | 3.01 mm |
| Diametru Conductor | 24.5 mm |
| Greutate Aluminiu | 848.3 kg/km |
| Greutate ACS | 329.6 kg/km |
| Greutate Conductor | 1177.9 kg/km |
| Rezistență Nominală | 109.2 kN |
| Rezistență Nominală HS | 96.3 kN |
| Rezistență DC @ 20°C | 0.0869 Ω/km |
| Capacitate Curent @ 85°C | 606 A |
| Capacitate Curent @150°C | 1280.5 A |
| Capacitate Curent @210°C | 1457 A |

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.