


ACSS/TW Conductor, 732.36mm², Dipper



Specificații

Nume Conductor	Dipper/ACSS/TW
Suprafață Secționată Fire Aluminiu	684.84 mm ²
Suprafață Secționată Fire Oțel	47.52 mm ²
Suprafață Secționată Conductor	732.36 mm ²
Nr. Fire Aluminiu	35
Nr. Fire Oțel	3
Diametru Fir Aluminiu	7 mm
Diametru Fir Oțel	2.94 mm
Diametru Conductor	31.90 mm
Greutate Aluminiu	1895.90 kg/km
Greutate Oțel	371.19 kg/km
Greutate Conductor	2267.09 kg/km
Rezistență Nominală	106.45 kN
Rezistență Nominală HS	115.00 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	129.74 kN
Rezistență DC @ 20°C	0.04070 Ω/km
Capacitate Curent @ 85°C	914 A
Capacitate Curent @ 200°C	1996 A
Capacitate Curent @ 250°C	2282 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.