

KTACSR/AW Conductor, 1646.70mm²



Specificații

Număr Fire Ktal	84
Număr Fire Oțel	7
Diametru Fir Ktal	4.80 mm
Diametru Fir Oțel	4.80 mm
Suprafață Secțională Fire Ktal	1520.0 mm ²
Suprafață Secțională Fire Oțel	126.67 mm ²
Suprafață Secțională Conductor	1646.70 mm ²
Diametru Conductor	52.80 mm
Greutate Ktal	4207.3 kg/km
Greutate Oțel	838.34 kg/km
Greutate Conductor	5045.6 kg/km
Rezistență Nominală HS	453.47 kN
Rezistență Nominală EHS	491.48 kN
Rezistență DC @ 20°C	0.0205 Ω/km
Capacitate Curent @ 85°C	1403.81 A
Capacitate Curent @ 150°C	2722.0 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.