


ACSS Conductor, 483mm², Towhee



Specificații

Nume Conductor	Towhee/ACSS
Aria secțiunii transversale	483 mm ²
Nr. fire aluminiu	48
Nr. fire otel	7
Diametru fir aluminiu	3.58 mm
Diametru fir otel	2.79 mm
Diametru Conductor	29.85 mm
Greutate Aluminiu	1337.1 kg/km
Greutate Otel	334.3 kg/km
Greutate Conductor	1671.4 kg/km
Rezistentă Nominală	88.2 kN
Rezistentă Nominală HS	95.9 kN
Rezistentă Nominală EHS	104.4 kN
Rezistentă Nominală UHS	109.1 kN
Rezistentă CC @ 20°C	0.057 Ω/km
Capacitate Curent @ 85°C	763 A
Capacitate curent @ 150°C	1650 A
Capacitate Curent @ 210°C	1884 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.