


ACSS Conductor, 725mm², Plover



Specificații

Nume Conductor	Plover/ACSS
Aria sectiunii transversale	725 mm ²
Nr. fire aluminiu	54
Nr. fire otel	19
Diametru fir aluminiu	4.14 mm
Diametru fir otel	2.48 mm
Diametru Conductor	37.21 mm
Greutate Aluminiu	2015.6 kg/km
Greutate Otel	718.3 kg/km
Greutate Conductor	2733.9 kg/km
Rezistenta Nominala	171.3 kN
Rezistenta Nominala HS	187.8 kN
Rezistenta Nominala EHS	206.2 kN
Rezistenta Nominala UHS	216.3 kN
Rezistenta CC @ 20°C	0.038 Ω/km
Capacitate Curent @ 85°C	969 A
Capacitate curent @ 150°C	2159 A
Capacitate Curent @ 210°C	2475 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.