


## ACSS Conductor, 1098mm<sup>2</sup>, Kiwi



### Specificații

Nume Conductor	Kiwi/ACSS
Aria sectiunii transversale	1098 mm <sup>2</sup>
Nr. fire aluminiu	72
Nr. fire otel	7
Diametru fir aluminiu	4.41 mm
Diametru fir otel	2.94 mm
Diametru Conductor	44.07 mm
Greutate Aluminiu	3052.2 kg/km
Greutate Otel	371.2 kg/km
Greutate Conductor	3423.4 kg/km
Rezistenta Nominala	130.4 kN
Rezistenta Nominala HS	138.9 kN
Rezistenta Nominala EHS	148.4 kN
Rezistenta Nominala UHS	153.6 kN
Rezistenta CC @ 20°C	0.026 Ω/km
Capacitate Curent @ 85°C	1217 A
Capacitate curent @ 150°C	2799 A
Capacitate Curent @ 210°C	3225 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.