



Solis-3P(5-10)K-4G-LV

Solis Three Phase Inverters



360 degree



Features:

- ▶ Max. efficiency 98.0%
- ▶ Wide voltage range and low startup voltage
- ▶ 2 MPPT design with precise MPPT algorithm
- ▶ THDi<1.5%, low harmonic distortion against grid
- ▶ Multiple protections levels
- ▶ Intergrated Export Power Manager (EPM)

Model:

220V: Solis-3P5K-4G-LV Solis-3P6K-4G-LV
Solis-3P10K-4G-LV

Datasheet

Model Name	Solis-3P5K-4G-LV	Solis-3P6K-4G-LV	Solis-3P10K-4G-LV		
Input DC					
Recommended max. PV power	7.5 kW	9 kW	15 kW		
Max. input voltage		1000 V			
Rated voltage		330 V			
Start-up voltage		180 V			
MPPT voltage range		160-500 V			
Max. input current	11 A / 11 A		22 A / 22 A		
Max. short circuit current	17.2 A / 17.2 A		34.3 A / 34.3 A		
MPPT number/Max. input strings number	2/2		2/4		
Output AC					
Rated output power	5 kW	6 kW	10 kW		
Max. apparent output power	5.5 kVA	6.6 kVA	11 kVA		
Max. output power	5.5 kW	6.6 kW	11 kW		
Rated grid voltage		3/PE, 208 V / 220 V / 240 V			
Rated grid frequency		50 Hz / 60 Hz			
Rated grid output current	13.1 A	15.7 A	26.2 A		
Max. output current	14.4 A	16.7 A	28.8 A		
Power Factor	>0.99 (0.8 leading - 0.8 lagging)				
THDi	<1.5%				
Efficiency					
Max. efficiency	98.0%				
EU efficiency	97.5%				
Protection					
DC reverse-polarity protection	Yes				
Short circuit protection	Yes				
Output over current protection	Yes				
Surge protection	Yes				
Grid monitoring	Yes				
Anti-islanding protection	Yes				
Temperature protection	Yes				
Integrated AFCI (DC arc-fault circuit protection)	Yes*				
Integrated DC switch	Optional				
General Data					
Dimensions (W*H*D)	310*563*219 mm				
Weight	18 kg		19.8 kg		
Topology	Transformerless				
Self consumption (night)	<1 W				
Operating ambient temperature range	-25 ~ +60°C				
Relative humidity	0-100%				
Ingress protection	IP65				
Cooling concept	Natural convection	Intelligent redundant fan-cooling			
Max. operation altitude	4000 m				
Grid connection standard	G98 or G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530				
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4				
Features					
DC connection	MC4 connector				
AC connection	Quick connection plug				
Display	LCD				
Communication	RS485, Optional: Wi-Fi, GPRS				

* Activation required.