

PRODUCT DATASHEET

SENSOR DALI-2 LIGHT/PRESENCE-6

INFRARED CEILING INTEGRATION

SENSOR DALI-2 LIGHT-PRESENCE-6 INFRARED CEILING INTEGRATION | DALI-2 input device, infrared presence detector with 6 m movement detection



Areas of application

- Single rooms
- Meeting, storage and break rooms
- Sanitary areas

Product benefits

- Quick and easy installation using spring clips
- Through-wiring using pre-assembled cable with WAGO connector
- Integrated DALI bus power supply (no mains connection required)
- Several sensors can be connected to a DALI line
- Can be integrated into lighting and building management systems that support DALI-2 sensors
- Compatible with LEDVANCE VIVARES DALI light management system

Product features

- DALI-2 certified light and presence sensor for ceiling installation
- Presence detection via passive IR element
- Detection height up to 3,7 m
- Function display with LED
- Detection area up-to 6 m

TECHNICAL DATA

Electrical data

Nominal wattage	0.20 W
Nominal voltage	16 V
Type of current	DC
Mains frequency	0 Hz

Dimensions & Weight



Length	83.00 mm
Width	83.00 mm
Height	32.00 mm
Diameter	83 mm
Cable cross-section, input side	0.2...1.3 mm ²
Wire preparation length, input side	7...9 mm
Product weight	80.00 g

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Ambient temperature range	0...+40 °C
Temperature range in operation	0...+40 °C


Capabilities

Dimmable	No
Dimming interface	DALI-2
Maximum installation height	3.7 m
Detection area	6 m
Max. presence detection area	6 m
Detection angle	360 °
Type of installation	Ceiling integration
Operating range, light sensor	5...550 lx

Certificates & Standards

Approval marks – approval	CE / UKCA / EAC
Protection class	II
Type of protection	IP20








Accessories Optional

Product image	Product name	EAN
	SENSOR CEILING MOUNTING KIT LIGHT/PRESENCE-6	4099854748714

Safety advice

- All electrical connections must be made by a qualified person.
- Disconnect mains before installation.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	SENSOR DALI-2 LS-PD-6 IR CI
	Legal information	Legal Insert DALI COMPONENTS
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Safety Insert G11210554
	Declarations of conformity	SENSOR DALI-2 LS-PD-4 IR CI
	Declarations of conformity UKCA	SENSOR DALI-2 LS-PD-4 IR CI
Tender texts		Document name
	Tender documents	DALI-2 SENSORS LIGHTPRESENCE-6 INFRARED CEILING INTEGRATION-EN

LOGISTICAL DATA



Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075837621	Folding box 1	45 mm x 86 mm x 100 mm	100.00 g	0.39 dm ³

503 Service Temporarily Unavailable

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075837638	Shipping box 20	245 mm x 192 mm x 225 mm	2274.00 g	10.58 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

– For current information see www.ledvance.com/light-management-systems

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.