


AACSR IEC 61089 -Type A3/S3A Conductor, 280.48mm² + 65.47mm²



Specificații

Nume Conductor	N/A
Aria Secțională Conductor	N/A mm ²
Aria Secțională Aliaj	280.48 mm ²
Aria Secțională Fire Oțel	65.47 mm ²
Aria Secțională Conductor	N/A mm ²
Număr Fire Aluminiu	30
Număr Fire Oțel	7
Diametru Fir Aluminiu	3.45 mm
Diametru Fir Oțel	3.189 mm
Diametru Conductor	24.18 mm
Greutate Aliaj	775.5 kg/km
Greutate Oțel	511.5 kg/km
Greutate Conductor	1286.7 kg/km
Rezistență Nominală	N/A kN
Clasa A Rezistență Nominală	171.6 kN
Clasa B Rezistență Nominală	166.12 kN
Rezistență DC @ 20°C	0.1203 Ω/km
Capacitate Curent @75°C	414 A
Capacitate Curent @85°C	520 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.