



AACSR IEC 61089 -Type A3/S3A Conductor, 399.98mm² + 91.07mm²



Specificații

Nume Conductor	N/A
Aria Secțională Conductor	N/A mm ²
Aria Secțională Aliaj	399.98 mm ²
Aria Secțională Fire Oțel	91.07 mm ²
Aria Secțională Conductor	N/A mm ²
Număr Fire Aluminiu	30
Număr Fire Oțel	19
Diametru Fir Aluminiu	4.174 mm
Diametru Fir Oțel	2.50 mm
Diametru Conductor	28.539 mm
Greutate Aliaj	1105.35 kg/km
Greutate Oțel	712.8 kg/km
Greutate Conductor	1818.3 kg/km
Rezistență Nominală	N/A kN
Clasa A Rezistență Nominală	237.6 kN
Clasa B Rezistență Nominală	231.7 kN
Rezistență DC @ 20°C	0.0844 Ω/km
Capacitate Curent @75°C	505 A
Capacitate Curent @85°C	643 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.